

Fax: +971-4-3391322/3391323 E-mail: bergrdxb@emirates.net.ae

شركة اصباغ بيرجر الامارات المحدودة (ذ.م.م.) BERGER PAINTS EMIRATES LIMITED تليفون: ۳۳۹۱۰۰۰-٤-۲۷۹+ فاکس: ۱۳۲۲/۳۳۹ ۳۳۹_٤_۱۹۷۱ E-mail: bergrdxb@emirates.net.ae



www.bergeronline.com

Material Safety Data Sheet

EPILUX 219 HB EPOXY

Part B

1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND COMPANY:

Product Name : Epilux 219 HB Epoxy Undercoat Part B

Product Type : For all shades

Supplier : Berger Paints Emirates Limited P O Box 27524, Dubai, UAE.

Telephone Number : 009714-391000 Emergency Telephone Number: 009714-391078

2. **COMPOSITION/INFORMATION ON INGREDIENTS:**

		Weight%	CAS Number	LEL Vol%	ACGIH TLV-TWA
•	Polyamine Resin	70 - 90			
•	2,4,6 Tris (Dimethyl	5 - 15	90-72-2	N/A	Not established
	aminomethyl) Pheno	1			
•	Mono amine	5 - 15	000112-24-3	1	Not established

3. **HAZARDS IDENTIFICATION:**

• Hazards identification of the preparation :

R-10

Harmful by inhalation and in contact with skin R-20/21

R-36/38 Irritating to eyes and skin

May cause sensitization by skin contact R-43

4. **FIRST AID MEASURES:**

General : Remove contaminated clothing.

First Aid - Inhalation : Remove to fresh air. If rapid recovery does not occur,

obtain medical attention.

First Aid - Skin : Remove contaminated clothing immediately. Wash skin

thoroughly with soap and water.

First Aid - Eye : Irrigate copiously with clean, fresh water for atleast

10 minutes, holding the eye lids apart and seek medical

First Aid - Ingestion : Do not induce vomiting. Obtain immediate medical

attention.

... (2) ..





Fax: +971-4-3391322/3391323 E-mail: bergrdxb@emirates.net.ae

شركة اصباغ بيرجر الامارات المحدودة (ذ.م.م.) BERGER PAINTS EMIRATES LIMITED صندوق برید ۲۷۵۲۶ دبی اع.م. تليفون: ۳۳۹۱۰۰۰ ع-۱۷۲۱ فاکس: ۱۳۲۲ ۳۳۹ ۱۳۲۳/۳۳۹ ۹۲۱ ۹۲۱ E-mail: bergrdxb@emirates.net.ae



www.bergeronline.com

5. **FIRE FIGHTING MEASURES:**

Specific hazards : Fire will produce dense, black smoke. Inhalation of

decomposition products may cause serious health hazards.

: Water spray-mist, foam, dry chemical powder, carbon Extinguishing media

dioxide, sand.

Unsuitable extinguishing media: Water in a jet.

6. **ACCIDENTAL RELEASE MEASURES:**

Personal precautions : Avoid contact with skin and eyes. Do not breathe

vapour. Extinguish naked flames. Remove ignition

sources. Avoid sparks.

Personal protection : Wear PVC gloves, safety boots. Wear full face-piece

> respiratory with organic vapour canister NPF 400. In a confined space, wear self-contained breathing apparatus

open circuit type NPF 2000.

: Prevent contamination of soil and water.

Environmental precautions

Processing for Cleaning/

Collecting : Contain and collect spillage with non-combustible

> absorbent materials, e.g., sand, earth or spill control material and place in a container for disposal according

to local regulation.

7. **HANDLING AND STORAGE:**

Avoid prolonged or repeated contact with skin. Do not breathe vapour, spray/mist. Extinguish any naked flames. Remove ignition sources. Avoid spark. Do not smoke. Take precautionary measures against static discharge.

Handling temperature : Ambient

Storage : Keep container tightly closed and in a well ventilated

place. Keep away from direct sunlight and other sources

of heat or ignition. Do not smoke in storage areas.

Storage temperature : Ambient.

8. **EXPOSURE CONTROL/PERSONAL PROTECTION:**

Engineering Control measures : Use only in well ventilated areas.

Respiratory protection : When workers are facing concentrations above the

exposure limit they must use appropriate certified

respirators.

: PVC Gloves. Barrier creams may help to protect the Hand protection

exposed areas of the skin.

: Use safety eyewear designed to protect against splash Eye protection

of products.

... (3) ..

9. **PHYSICAL AND CHEMICAL PROPERTIES:**





Fax: +971-4-3391322/3391323 E-mail: bergrdxb@emirates.net.ae

شركة اصباغ بيرجر الامارات المحدودة (ذ.م.م.) BERGER PAINTS EMIRATES LIMITED صندوق برید ۲۷۰۲۶ دبی ا.ع.م. تليفون: ۳۳۹۱۰۰۰ ع-۱۹۷۱ فاکس: ۱۳۲۲/۳۳۹ ۳۳۹_٤_۱۹۷۱ E-mail: bergrdxb@emirates.net.ae



www.bergeronline.com

Physical state : Liquid Odour : Aromatic Safety related information Value

Flash Point : 135 °C (closed cup)

Ignition temperature $: > 320^{\circ}C$

Initial Boiling Point : 135°C (Based on TETA)

: Heavier Vapour Density (Vs. Air) Evaporation Rate (Vs. n-Bu. Acetate) : Slower : 0.85 - 0.95 Density at 25°C Solubility in water : Partly miscible

STABILITY/REACTIVITY: 10.

Stability : Stable under normal conditions.

Conditions to avoid : Heat, flames and sparks.

Materials to avoid : Strong Oxidising agents, strong acids and strong bases : Burning produces obnoxious and toxic fumes, carbon Hazardous decomposition

products oxides and nitrogen oxides.

11. **TOXICOLOGICAL INFORMATION:**

Basis for assessment : This product was not tested but the information given is

based on the known toxicological data of the constituents

: LD 50 > 2000 mg/kg based on Xylene Acute toxicity - Oral : LD 50 > 2000 mg/kg based on Xylene Acute dermal irritation Acute toxicity - inhalation : LC 50 > 5 mg/l based on Xylene

Eye irritation : Irritant Skin irritation : Irritant

12. **ECOLOGICAL INFORMATION:**

Water contamination class : Do not contaminates surface water

13. **DISPOSAL CONSIDERATIONS:**

Precautions : Refer to Section 7

Waste disposal : Recover or recycle if possible. Otherwise incineration. Container disposal : Allow the residue to dry and dispose of as scrap metal.

TRANSPORT INFORMATION: 14.

UN Number : 1263 : 3.3 **IMCO Class** Page Number : 3149 Marine Pollutant : Yes Proper shipping name : Paint

... (4) ..





Fax: +971-4-3391322/3391323 E-mail: bergrdxb@emirates.net.ae

شركة اصباغ بيرجر الامارات المحدودة (ذ.م.م.) BERGER PAINTS EMIRATES LIMITED تليفون: ۳۳۹۱۰۰۰ ع-۱۹۳۱ فاکس: ۱۳۲۲/۳۳۹ ۳۳۹_٤_۱۹۷۱ E-mail: bergrdxb@emirates.net.ae



www.bergeronline.com

15. **REGULATORY INFORMATION:**

EC Classification : Flammable, Harmful.

Contains : Xylene, 2,4,6 Tris (dimethyl amino methyl) phenol

• EC Risk phrases

R-10 : Flammable

R-20/21: Harmful by inhalation and in contact with skin

R-36/38 : Irritating to eyes and skin

R-43 : May cause sensitisation by skin contact

• EC Safety Phrases

S-24/25 : Avoid contact with skin and eyes.

: Wear suitable protective clothing, gloves and eyes S-36/37/39

and face protector.

16. **DISCLAIMER**:

This information is based on our current knowledge and is obtained from sources which we believe are reliable. However, the information is provided without any warranty, express or implied, regarding the correctness. This information is extended to describe the product for the purposes of health, safety and environmental requirements only. The conditions or methods of handling, storage, use or disposal of the product are beyond our control. For this and other reasons, we do not assume responsibility and expressly disclaim liability for loss, damage connected with the handling, storage, use or disposal of the product.