

**Material Safety Data Sheet**
**EPILUX 66**
**Part – B (Hardener)**
**1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND COMPANY :**

Product Name : Epilux 66 Hardener  
Product Type : Red Oxide  
Supplier : Berger Paints Emirates Limited  
P O Box 27524  
Dubai, UAE.  
Telephone Number : 00-9714-3391000  
Emergency Telephone Number : 00-9714-3391078

**2. COMPOSITION/INFORMATION ON INGREDIENTS :**

	<u>Weight %</u>	<u>CAS Number</u>	<u>LEL Vol %</u>	<u>ACGIH TLV-TWA</u>
• Polyamide Resin	20 - 30	-	-	-
• Toluene	50 - 60	-	-	-
• Iso-Propyle Alcohol	20 - 30	67-63-0	-	500 ppm

**3. HAZARDS IDENTIFICATION :**

- Hazards identification of the preparation :  
R-10 : Flammable  
R-20/21 : Harmful by inhalation and in contact with skin.  
R-36-38 : Irritating to eyes and skin.  
R-43 : May cause sensitization by skin contact

**4. FIRST AID MEASURES :**

General : Remove contaminated clothing  
First Aid - Inhalation : Remove to fresh air. If rapid recovery does not occur, obtain medical attention.  
First Aid - Skin : Remove contaminated clothing immediately. Wash skin thoroughly with soap and water.  
First Aid - Eye : Irrigate copiously with clean, fresh water for atleast 10 minutes, holding the eye lids apart and seek medical advice.  
First Aid - Ingestion : Do not induce vomiting. Obtain immediate medical attention.

... (2) ..

**5. FIRE FIGHTING MEASURES :**

- Specific hazards : Fire will produce dense, black smoke, inhalation of decomposition products may cause serious health hazards.
- Extinguishing media : Water spray - mist, foam, dry chemical powder, carbondioxide, sand.
- Unsuitable extinguishing media : Water in a jet.

**6. ACCIDENTAL RELEASE MEASURES :**

- Personal precautions : Avoid contact with skin and eyes. Do not breathe vapour. Extinguish naked flames. Remove ignition sources, Avoid sparks.
- Personal protection : Wear PVC gloves, safety boots. Wear full face - place respirator with organic vapour canister NPF 400. In a confined space, wear self-contained breathing apparatus open circuit type NPF 2000.
- Environmental precautions : Prevent contamination of soil and water.
- Processing for Cleaning/Collecting : Contain and collect spillage with non-combustible absorbent materials, e.g., sand, earth or spill control material and place in a container for disposal according to local regulation.

**7. HANDLING AND STORAGE :**

Avoid prolonged or repeated contact with skin. Do not breathe vapour, spray/mists. Extinguish any naked flames. Remove ignition sources. Avoid spark. Do not smoke. Take precautionary measures against static discharges.

- Handling temperature : Ambient
- Storage : Keep container tightly closed and in a well ventilated place. Keep away from direct sunlight and other sources of heat or ignition. Do not smoke in storage areas.
- Storage temperature : Ambient.

**8. EXPOSURE CONTROL/PERSONAL PROTECTION :**

- Engineering Control Measures : Use only in well ventilated areas.
- Respiratory protection : When workers are facing concentrations above the exposure limit they must use appropriate certified respirators.
- Hand protection : PVC Gloves. Barrier creams may help to protect the exposed areas of the skin.
- Eye protection : Use safety eyewear designed to protect against splash of products.

... (3) ..

**9. PHYSICAL AND CHEMICAL PROPERTIES :**

Physical status	: Liquid
Odour	: Aromatic
<u>Safety related information</u>	: <u>Value</u>
Flash Point	: 23 - 29°C (Abel closed cup)
Ignition temperature	: > 350°C
Initial Boiling Point	: 137°C (Based on Xylene)
Vapour Density (Vs Air)	: Heavier
Evaporation Rate (vs.n-Bu.Acetate)	: Slower
Density at 25°C	: 0.85 - 0.95 gm/cc
Solubility in water	: Partly miscible

**10. STABILITY/REACTIVITY :**

Stability	: Stable under normal conditions.
Conditions to avoid	: Heat, flames and sparks.
Materials to avoid	: Strong oxidising agents, strong acids and strong bases.
Hazardous decomposition products	: Burning produces obnoxious and toxic fumes, carbon oxides and nitrogen oxides.

**11. TOXICOLOGICAL INFORMATION :**

Basis for assessment	: This product was not tested but the information given is based on the known toxicological data of the constituents.
Acute toxicity - oral	: LD 50 > 200 mg/kg based on Xylene
Acute toxicity - irritation	: LD 50 > 200 mg/kg based on Xylene
Acute toxicity - inhalation	: LC 50 > 5 mg/l based on Xylene
Eye irritation	: Irritant.
Skin irritation	: Irritant.

**12. ECOLOGICAL INFORMATION**

Water contamination class	: Do not contaminates surface water.
---------------------------	--------------------------------------

**13. DISPOSAL CONSIDERATIONS :**

Precautions	: Refer to Section 7
Waste disposal	: Recover or recycle if possible. Otherwise incineration.
Container disposal	: Allow the residue to dry and dispose of as scrap metal.

... (4) ..

**14. TRANSPORT INFORMATION :**

UN Number : 1263  
IMCO Class : 3.3  
Page Number : 3149  
Marine Pollutant : Yes  
Proper shipping name : Paint

**15. REGULATORY INFORMATION :**

- EC Classification : Flammable, Harmful  
Contains : Xylene, 2, 4, 6 Tris (dimethyl amino methyl) phenol
- EC Risk Phrases  
R-10 : Flammable  
R-20/21 : Harmful by inhalation and in contact with skin  
R-36/38 : Irritating to eyes and skin  
R-43 : May cause sensitization by skin contact
- EC Safety Phrases  
S 24/25 : Avoid contact with skin and eyes  
S 36/37/39 : Wear suitable protective clothing, gloves and eyes and face protector.

**16. DISCLAIMER :**

This information is based on our current knowledge and is obtained from sources which we believe are reliable. However, the information is provided without any warranty, express or implied, regarding the correctness. This information is extended to describe the product for the purposes of health, safety and environmental requirements only. The conditions or methods of handling, storage, use or disposal of the product are being our control. For this and other reasons, we do not assume responsibility and expressly disclaim liability for loss, damage connected with the handling, storage, use or disposal of the product.