

**Material Safety Data Sheet**
**EPILUX 8**
**1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND COMPANY**

Product Name : Epilux 8  
 Product Type : Polyamine cured High Build Coal Tar Epoxy  
 Supplier : Berger Paints Emirates Limited  
 P O Box 27524, Dubai, UAE  
 Telephone Number : 009714-3391000  
 Emergency Telephone Number : 009714-3391078

**2. COMPOSITION/INFORMATION ON INGREDIENTS OF MIXTURES :**

	Weight%	CAS Number	LEL Vol%	ACGIH TLV-TWA
• Epoxy Resin	18 – 28			
• Coal Tar	30 – 40	N/A		
• Heavy Naptha	5 - 10	64742-94-5	0.6	N/A
• Crystalline Silica	0 – 20	14808-60-7	NA	0.1 mg/m <sup>3</sup>
• Talc	20 - 40	14807-96-6	NA	2.0 mg/m <sup>3</sup>
• Xylene	2 – 5	1330-20-7	1.2	100 ppm
• Polyamine	5 – 15	N/E	N/E	N/E
• n-Butanol	1 - 3	71-36-3	1.4	50 ppm

**3. HAZARDS IDENTIFICATION :**

- Hazards identification of the preparation :  
 R-10 : Flammable.  
 R-20/21 Harmful by inhalation and in contact with skin.  
 R-38 Irritating to skin.  
 R-45 May cause cancer.

**4. FIRST AID MEASURES :**

- General : Remove contaminated clothing.
- First Aid - Inhalation : Remove to fresh air. If rapid recovery does not occur, obtain medical attention.
- First Aid - Skin : Remove contaminated clothing immediately. Wash skin thoroughly with soap and water.
- First Aid - Eye : Irrigate copiously with clean, fresh water for atleast 10 minutes, holding the eye lids apart and seek medical advice.
- First Aid - Ingestion : Do not induce vomiting. Obtain immediate medical attention.

... (2) ..

5. **FIRE FIGHTING MEASURES :**

- Specific hazards : Fire will produce dense, black smoke. Inhalation of decomposition products may cause serious health hazards.
- Extinguishing media : Water spray-mist, foam, dry chemical powder, carbon dioxide, sand.
- Unsuitable extinguishing media : Water in a jet.

6. **ACCIDENTAL RELEASE MEASURES :**

- Personal precautions : Avoid contact with skin and eyes. Do not breathe vapour. Extinguish naked flames. Remove ignition sources. Avoid sparks.
- Personal protection : Wear PVC gloves, safety boots. Wear full face-piece respirator with organic vapour canister NPF 400. In a confined space, wear self-contained breathing apparatus open circuit type NPF 2000.
- Environmental precautions : Prevent contamination of soil and water.
- Processing for Cleaning/  
Collecting : Contain and collect spillage with non-combustible absorbent materials, e.g., sand, earth or spill control material and place in a container for disposal according to local regulation

7. **HANDLING AND STORAGE:**

Avoid prolonged or repeated contact with skin. Do not breathe vapour, spray/mists. Extinguish any naked flames. Remove ignition sources. Avoid spark. Do not smoke. Take precautionary measures against static discharges.

- Handling temperature : Ambient
- Storage : Keep container tightly closed and in a well ventilated place. Keep away from direct sunlight and other sources of heat or ignition. Do not smoke in storage areas.
- Storage temperature : Ambient.

8. **EXPOSURE CONTROLS/PERSONAL PROTECTION :**

- Engineering Control measures : Use only in well ventilated areas.
- Respiratory protection : When workers are facing concentrations above the exposure limit they must use appropriate certified respirators.
- Hand protection : PVC gloves. Barrier creams may help to protect the exposed areas of the skin.
- Eye protection : Use safety eyewear designed to protect against splash of products.

... (3) ..

## 9. PHYSICAL AND CHEMICAL PROPERTIES OF MIXTURES :

Physical state	: Liquid
Odour	: Like organic solvents
<u>Safety related information :</u>	<u>Value</u>
Flash Point	> 60°C
Ignition temperature	> 450°C
Initial Boiling Point	167°C (Based on Heavy Naptha)
Vapour Density (Vs. Air)	Heavier
Evaporation Rate (Vs. n-Bu. Acetate)	Slower
Density at 25°C	1.4 - 1.6 gm/cc
Solubility in water	Negligible

## 10. STABILITY/REACTIVITY :

Stability	: Stable under normal conditions.
Conditions to avoid	: Heat, flames and sparks. Caustic soda induce a vigorous polymerisation at a temperature around 200°C
Materials to avoid	: Strong Oxidising agents. Strong acids.
Hazardous decomposition products	: Carbon dioxide, Carbon Monoxide, Ammonia and Nitrogen oxides.

## 11. TOXICOLOGICAL INFORMATION :

Basis for assessment	: This product was not tested but the information given is based on the known toxicological data of the constituents. Short term exposure to high concentrations of vapours May cause irritation to the nose, throat or eyes. Headache and nausea are also possible. Long term Exposure to high concentrations of vapour may result In damage to the internal organs. Splashes to the skin Should be prevented since this may cause irritation. (Based on Coaltar)
----------------------	---

## 12. ECOLOGICAL INFORMATION

Water contamination class	: 2 (self classification)
---------------------------	---------------------------

## 13. DISPOSAL CONSIDERATIONS :

Precautions	: Refer to Section 7
Waste disposal	: Recover or recycle if possible. Otherwise incineration.
Container disposal	: Allow the residue to dry and dispose of as scrap metal.

... (4) ..

**14. TRANSPORT INFORMATION :**

UN Number : 1263  
IMCO Class : 3.3  
Page Number : 3149  
Marine Pollutant : Yes  
Proper shipping name : Paint

**15. REGULATORY INFORMATION :**

- EC Classification : Flammable, Harmful  
Contains : Heavy Naptha
- EC Risk phrases  
R-10 : Flammable.  
R-45 : May occur cancer  
R-20/21 : Harmful by inhalation and in contact with skin  
R-38 : Irritating to skin
- EC Safety Phrases  
S-24/25 : Avoid contact with skin and eyes.  
S-36/37 : Wear suitable protective clothing and gloves  
S51 : Use only in well ventilated areas.  
S-53 : Avoid exposure - obtain special instruction before use  
S-45 : In case of accident or feel unwell, seek medical advice immediately.

**16. DISCLAIMER :**

This information is based on our current knowledge and is obtained from sources which we believe are reliable. However, the information is provided without any warranty, express or implied, regarding the correctness. This information is extended to describe the product for the purposes of health, safety and environmental requirements only. The conditions or methods of handling, storage, use or disposal of the product are beyond our control. For this and other reasons, we do not assume responsibility and expressly disclaim liability for loss, damage connected with the handling, storage, use or disposal of the product.