

Fax: +971-4-3391322/3391323 E-mail: bergrdxb@emirates.net.ae

شركة اصباغ بيرجر الامارات المحدودة (ذ.م.م.) BERGER PAINTS EMIRATES LIMITED تليفون: ۳۳۹۱۰۰۰-٤-۲۷۹+ فاکس: ۱۳۲۲/۳۳۹ ۳۳۹_٤_۱۹۷۱ E-mail: bergrdxb@emirates.net.ae



www.bergeronline.com

Material Safety Data Sheet

LUXAPRIME 1400

IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND COMPANY 1.

Product Name : Luxaprime 1400 Product Type : Zinc Phosphate Primer

Supplier : Berger Paints Emirates Limited

P O Box 27524, Dubai, UAE

: 009714-3391000 Telephone Number Emergency Telephone Number: 009714-3391078

2. **COMPOSITION/INFORMATION ON INGREDIENTS:**

	Weight%	CAS Number	LEL Vol%	ACGIH TLV-TWA
 Alkyd Resin 	< 25			
 Zinc Phosphate 	< 15	7440-38-2	-	0.15 mg/m^3
• Talc	< 15	14807-96-6	-	2.00 mg/m^3
 Barium Sulphate 	< 10	7727-43-7	-	6.00 mg/m^3
 China Clay 	< 10	-	-	-
• Iron Oxide	< 10	1309-37-1	-	10.00 mg/m^3
 Lead Octoate 	< 0.4	7319-86-0	-	0.15 mg pb/m^3
 Calcium Octoate 	< 0.2	6107-56-8	-	-
 Cobalt Octoate 	< 0.2	136-52-7	-	0.05 mg Co/m^3
• Methyl Ethyl Ketoxime	< 0.2	96-29-7	1.9	10 mg/m^3
• Aliphatic Hydrocarbon	< 30	64742-82-1	1.0	525 mg/m^3

3. **HAZARDS IDENTIFICATION:**

• Hazards identification of the preparation :

R-10 : Flammable

R-51/53 Toxic to aquatic organisms may cause long-term

adverse effects in the aquatic environment.

4. FIRST AID MEASURES:

> General : Remove contaminated clothing.

First Aid - Inhalation : Remove to fresh air. If rapid recovery does not occur,

obtain medical attention.

First Aid - Skin : Remove contaminated clothing immediately. Wash skin

thoroughly with soap and water.

: Irrigate copiously with clean, fresh water for atleast 10 First Aid - Eye

minutes, holding the eye lids apart and seek medical

First Aid - Ingestion : Do not induce vomiting. Obtain immediate medical

attention.

... (2) ..





Fax: +971-4-3391322/3391323 E-mail: bergrdxb@emirates.net.ae

شركة اصباغ بيرجر الامارات المحدودة (ذ.م.م.) BERGER PAINTS EMIRATES LIMITED تليفون: ۳۳۹۱۰۰۰ ع-۱۹۷۱ فاکس: ۱۳۲۲/۳۳۹ ۳۳۹ ۹۲۲۲ +۹۷۱ E-mail: bergrdxb@emirates.net.ae



www.bergeronline.com

5. **FIRE FIGHTING MEASURES**:

Specific hazards : Fire will produce dense, black smoke. Inhalation of

decomposition products may cause serious health

hazards.

Extinguishing media : Water spray-mist, foam, dry chemical powder, carbon

dioxide, sand.

Unsuitable extinguishing media: Water in a jet.

6. **ACCIDENTAL RELEASE MEASURES:**

Personal precautions : Avoid contact with skin and eyes. Do not breathe

vapour. Extinguish naked flames. Remove ignition

sources. Avoid sparks.

: Wear PVC gloves, safety boots. Wear full face-piece Personal protection

> respirator with organic vapour canister NPF 400. In a confined space, wear self-contained breathing apparatus

open circuit type NPF 2000.

Environmental precautions

Processing for Cleaning/

Collecting

: Prevent contamination of soil and water.

: Contain and collect spillage with non-combustible

absorbent materials, e.g., sand, earth or spill control material and place in a container for disposal

according to local regulation.

7. HANDLING AND STORAGE:

Avoid prolonged or repeated contact with skin. Do not breathe vapour, spray/mists. Extinguish any naked flames. Remove ignition sources. Avoid spark. Do not smoke. Take precautionary measures against static discharges.

Handling temperature : Ambient

: Keep container tightly closed and in a well ventilated Storage

place. Keep away from direct sunlight and other sources

of heat or ignition. Do not smoke in storage areas.

Storage temperature : Ambient.

8. **EXPOSURE CONTROLS/PERSONAL PROTECTION:**

Engineering Control measures : Use only in well ventilated areas.

Respiratory protection : When workers are facing concentrations above the

exposure limit they must use appropriate certified

respirators.

: PVC gloves. Barrier creams may help to protect the Hand protection

exposed areas of the skin.

Eye protection : Use safety eyewear designed to protect against splash

of products.

... (3) ..





Fax: +971-4-3391322/3391323 E-mail: bergrdxb@emirates.net.ae

شركة اصباغ بيرجر الامارات المحدودة (ذ.م.م.) BERGER PAINTS EMIRATES LIMITED تليفون: ۳۳۹۱۰۰۰ ع-۱۹۷۱ فاکس: ۱۳۲۲/۳۳۹ ۳۳۹ ۹۲۲۲ +۹۷۱ E-mail: bergrdxb@emirates.net.ae



www.bergeronline.com

9. **PHYSICAL AND CHEMICAL PROPERTIES:**

Physical state : Liquid

Odour : Like organic solvents

Safety related information: Value Flash Point 35 - 43°C Ignition temperature 240 - 252°C **Boiling Point** 160 - 197°C Vapour Density (Vs. Air) Heavier

Evaporation Rate (Vs. n-Bu. Acetate): Slower Density at 25°C 1.40 - 1.50 Gm/cc

Solubility in water In soluble.

10. **STABILITY/REACTIVITY**:

Stability : Stable under normal use conditions. Polymerised in

presence of oxygen.

Conditions to avoid : Heat, flames and sparks

Materials to avoid : Unknown : Unknown Hazardous decomposition

products

11. **TOXICOLOGICAL INFORMATION:**

Basis for assessment : This product was not tested but the information

given is based on the known toxicological data

of the constituents.

: LD 50 expected to be above 2000 mg/kg Acute toxicity - oral Acute toxicity - dermal : LD 50 expected to be above 2000 mg/kg

Acute toxicity - inhalation : LC 50 expected to be > 5 mg/l

: The liquid splashed in the eyes may cause irritation. Eye irritation Skin irritation : Not a skin sensitiser but prolonged contact with the

preparation may cause removal of natural fat from the

skin resulting to dermatitis.

12. **ECOLOGICAL** : Avoid contamination of earth, rivers, lakes or sewages

INFORMATION

Water contamination class : 2 (self classification)

13. **DISPOSAL CONSIDERATIONS:**

Precautions : Refer to Section 7

: Recover or recycle if possible. Otherwise incineration. Waste disposal Container disposal : Allow the residue to dry and dispose of as scrap metal.

... (4) ..





Fax: +971-4-3391322/3391323 E-mail: bergrdxb@emirates.net.ae

شركة اصباغ بيرجر الامارات المحدودة (ذ.م.م.) BERGER PAINTS EMIRATES LIMITED تليفون: ۳۳۹۱۰۰۰ ع-۱۷۲ فاکس: ۱۳۲۲/۳۳۹ ۳۳۹_٤_۱۹۷۱ E-mail: bergrdxb@emirates.net.ae



www.bergeronline.com

14. TRANSPORT INFORMATION:

UN Number : 1263 **IMCO Class** : 3.3 Page Number : 3149 Marine Pollutant : Yes : Paint Proper shipping name

15. **REGULATORY INFORMATION:**

• EC Classification : Flammable dangerous for the environment

Contains : White Spirit

EC Risk phrases

R10 : Flammable.

R51/53 : Toxic to aquatic organisms, may cause long

term adverse effects in the aquatic environment.

EC Safety Phrases

S61 : Avoid release to the environment.

S24 : Avoid contact with skin

S26 : In case of contact with eyes, rinse immediately

with plenty of water and seek medical advice.

S51 : Use only in well ventilated areas.

16. **DISCLAIMER:**

This information is based on our current knowledge and is obtained from sources which we believe are reliable. However, the information is provided without any warranty, express or implied, regarding the correctness. This information is extended to describe the product for the purposes of health, safety and environmental requirements only. The conditions or methods of handling, storage, use or disposal of the product are beyond our control. For this and other reasons, we do not assume responsibility and expressly disclaim liability for loss, damage connected with the handling, storage, use or disposal of the product.

