

شركة اصباغ بيرجر الامارات المحدودة (ذ.م.م.) BERGER PAINTS EMIRATES LIMITED P.O. Box 27524 Dubai U.A.E. Tel.: +971-4-3391000 Fax: +971-4-3391322/3391323 E-mail: bergrdxb@emirates.net.ae

صندوق بريد ۲۷۰۲٤ دبي ا.ع.م. تليفون: ٣٣٩١٠٠٠-٤-١٧٩+ فاکس : ۹۷۱-٤-۳۳۹۱۳۲۲/۳۳۹۱۳۲۲ + E-mail: bergrdxb@emirates.net.ae



www.bergeronline.com

Material Safety Data Sheet

LUXATHANE 6050

Hardener

1. **IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND COMPANY :**

Product Name	:	Luxathane 6050 Hardener
Product Type	:	For all shades
Supplier	:	Berger Paints Emirates Limited
		P O Box 27524, Dubai, UAE.
Telephone Number	:	009714-391000
Emergency Telephone Number	:	009714-391078

2. **COMPOSITION/INFORMATION ON INGREDIENTS :**

	Weight%	CAS Number	LEL Vol%	ACGIH TLV-TWA
• HDI Biuret	< 75	4035-89-6		1 ppm
• Xylene	< 20	1330-20-7	1.2	100 ppm
Butyl Acetate	< 10			

3. HAZARDS IDENTIFICATION :

•	Hazards identification of the pr	reparation :
	R-10 :	Flammable
	R-20/21	Harmful by inhalation and in contact with skin
	R-36/38	Irritating to eyes and skin
	R-43	May cause sensitisation by skin contact

4. FIRST AID MEASURES :

General	: Remove contaminated clothing.
First Aid - Inhalation	: Remove to fresh air. If rapid recovery does not occur, obtain medical attention.
First Aid - Skin	: Remove contaminated clothing immediately. Wash skin thoroughly with soap and water.
First Aid - Eye	: Irrigate copiously with clean, fresh water for atleast 10 minutes, holding the eye lids apart and seek medical advice.
First Aid - Ingestion	: Do not induce vomiting. Obtain immediate medical attention.
	(2)





Berger International: Bahrain: Barbados, China, Hong Kong, Jamaica, Malaysia, Myanmar, Singapore, Thailand, Trinidad & Tobago, UAE Taubmans: Fiji Asian Paints: Bangladesh, India, Nepal, Oman, Sri Lanka Apco Coatings: Australia, Fiji, Solomon Islands, Tonga, Vanuatu Scib Paints: Egypt



شركة اصباغ بيرجر الامارات المحدودة (ذ.م.م.) BERGER PAINTS EMIRATES LIMITED P.O. Box 27524 Dubai U.A.E. Tel.: +971-4-3391000 Fax: +971-4-3391322/3391323 E-mail: bergrdxb@emirates.net.ae

صندوق بريد ٢٧٥٢٤ دبي ا.ع.م. تليفون: ٣٣٩١٠٠٠-٤-١٧٩+ فاکس : ۳۲۹۱۳۲۲/۳۳۹۱۳۲۲ +۹۷۱ E-mail: bergrdxb@emirates.net.ae



www.bergeronline.com

5. **FIRE FIGHTING MEASURES**:

Specific hazards	: Fire will produce dense, black smoke. Inhalation of decomposition products may cause serious health hazards.
Extinguishing media	: Water spray-mist, foam, dry chemical powder, carbon
	dioxide, sand.
Unsuitable extinguishing media	: Water in a jet.

6. **ACCIDENTAL RELEASE MEASURES :**

Personal precautions	: Avoid contact with skin and eyes. Do not breathe vapour. Extinguish naked flames. Remove ignition sources. Avoid sparks.
Personal protection	: Wear PVC gloves, safety boots. Wear full face-piece respiratory with organic vapour canister NPF 400. In a confined space, wear self-contained breathing apparatus open circuit type NPF 2000.
Environmental precautions Processing for Cleaning/	: Prevent contamination of soil and water.
Collecting	: Contain and collect spillage with non-combustible absorbent materials, e.g., sand, earth or spill control material and place in a container for disposal according to local regulation.

7. HANDLING AND STORAGE :

Avoid prolonged or repeated contact with skin. Do not breathe vapour, spray/mist. Extinguish any naked flames. Remove ignition sources. Avoid spark. Do not smoke. Take precautionary measures against static discharge.

Handling temperature	: Ambient
Storage	: Keep container tightly closed and in a well ventilated
	place. Keep away from direct sunlight and other sources of heat or ignition. Do not smoke in storage areas.
Storage temperature	: Ambient.

8. **EXPOSURE CONTROL/PERSONAL PROTECTION :**

Engineering Control measures Respiratory protection	 Use only in well ventilated areas. When workers are facing concentrations above the exposure limit they must use appropriate certified respirators.
Hand protection	: PVC Gloves. Barrier creams may help to protect the exposed areas of the skin.
Eye protection	: Use safety eyewear designed to protect against splash of products.





شركة اصباغ بيرجر الامارات المحدودة (ذ.م.م.) BERGER PAINTS EMIRATES LIMITED P.O. Box 27524 Dubai U.A.E. Tel.: +971-4-3391000 Fax: +971-4-3391322/3391323 E-mail: bergrdxb@emirates.net.ae

صندوق بريد ۲۷۵۲٤ دبي اعم. تليفون: ٣٣٩١٠٠٠-٤-٩٧١ فاكس : ٣٣٩١٣٢٢/٣٣٩١٣٢٢ -٤-١٩٧+ E-mail: bergrdxb@emirates.net.ae



www.bergeronline.com

9. **PHYSICAL AND CHEMICAL PROPERTIES :**

Physical state	: Liquid
Odour	: Aromatic
Safety related information	Value
Flash Point	: 23 - 29°C (Abel closed cup)
Ignition temperature	: > 310°C
Initial Boiling Point	: 137°C (Based on Xylene)
Vapour Density (Vs. Air)	: Heavier
Evaporation Rate (Vs. n-Bu. Acetate)	: Slower
Density at 25°C	: 0.95 – 1.02 gm/cc
Solubility in water	: Partly miscible

10. **STABILITY/REACTIVITY**:

Stability	: Stable under normal conditions.
Conditions to avoid	: Heat, flames and sparks.
Materials to avoid	: Alcohols, Amines, Bases, Water and aqueous solution.
	With a great release of CO_2 , and hence a risk of a
	pressure build-up in confined areas.
Hazardous decomposition	: On combustion or on thermal decomposition
products	(pyrolysis) releases toxic gases e.g., Carbon Oxides
	(CO+CO ₂) Nitrogen Oxides

11. **TOXICOLOGICAL INFORMATION :**

Basis for assessment Acute toxicity - Oral	 This product was not tested but the information given is based on the known toxicological data of the constituents LD 50 > 2000 mg/kg based on Xylene;
Acute dermal irritation	LD $50 > 5000 \text{ mg/kg}$ based on HDI biuret : LD $50 > 2000 \text{ mg/kg}$ based on Xylene
Acute toxicity - inhalation	: Harmful
Eye irritation	: Harmful
Skin irritation	: Harmful
Local effects	: At high concentrations, the vapour can be irritating to the respiratory system Repeated or prolonged contact may cause slight irritation to the skin. May cause irritation to the eyes.
Sensitization	: May cause respiratory sensitization (asthma) on prolonged or repeated exposure to people who are sensitized to, or have already been sensitised to, the product.

12. **ECOLOGICAL INFORMATION**:

Water contamination class : Avoid water contamination.

... (4) ..





BERGER PAINTS EMIRATES LIMITED P.O. Box 27524 Dubai U.A.E. Tel.: +971-4-3391000 Fax: +971-4-3391322/3391323 E-mail: bergrdxb@emirates.net.ae

شركة اصباغ بيرجر الإمارات المحدودة (ذ.م.م.) صندوق بريد ٢٧٥٢٤ دبي ا.ع.م. تليفون: ٣٣٩١٠٠٠ ٤- ٩٧١ فلكس : ٣٣٩١٣٢٢/٣٣٩١٣٢٢ ٤- ٩٧١ E-mail: bergrdxb@emirates.net.ae



www.bergeronline.com

13. **DISPOSAL CONSIDERATIONS** :

Precautions	: Refer to Section 7
Waste disposal	: Recover or recycle if possible. Otherwise incineration.
Container disposal	: Allow the residue to dry and dispose of as scrap metal.

14. **TRANSPORT INFORMATION** :

UN Number	:	1263
IMCO Class	:	3.3
Page Number	:	3149
Marine Pollutant	:	Yes
Proper shipping name	:	Paint

15. **<u>REGULATORY INFORMATION</u>** :

	Flammable, Harmful. Xylene, HDI biuret.
• EC Risk phrases	
*	Flammable
R-20/21 :	Harmful by inhalation and in contact with skin
R-36/38 :	Irritating to eyes and skin
R-43 :	May cause sensitisation by skin contact
• EC Safety Phrases	
S-7/8 :	Keep container tightly closed and dry
S-24/25 :	Avoid contact with skin and eyes.
S-36/37/39 :	Wear suitable protective clothing, gloves and eyes and face protector.

16. **DISCLAIMER** :

This information is based on our current knowledge and is obtained from sources which we believe are reliable. However, the information is provided without any warranty, express or implied, regarding the correctness. This information is extended to describe the product for the purposes of health, safety and environmental requirements only. The conditions or methods of handling, storage, use or disposal of the product are beyond our control. For this and other reasons, we do not assume responsibility and expressly disclaim liability for loss, damage connected with the handling, storage, use or disposal of the product.

